

Oden

LED Luminaire







Oden LED

The Oden takes versatility to new heights with a modular luminaire concept for virtually endless design combinations. 6 dramatic cast cap styles can be matched with any of 6 elegant spun shade styles. You have the freedom to create your distinctive look and feel for your lighting project. The Oden Luminaire can be matched with a variety of complementary decorative mounting arms, wall brackets and poles. Each Oden cast aluminum cap and spun aluminum shade is meticulously crafted and finished to the highest quality standards. Attention to detail, use of the finest materials, and expert manufacturing techniques assure Oden luminaires will provide beauty and enduring performance in any environment. To top it off the Oden comes with a 5 year limited warranty, 5 year warranty on the finish. For full warranty information, please visit visionairelighting.com

Features

- High-performance Type I, Type II, Type III, Type IV, Type V and Type VW optics.
- 6 interchangeable spun aluminum shade styles
- 6 unique durable cast aluminum top caps
- 36 possible combinations for a completely customizable fixture
- Offered in your choice of 16-128 LED
- 3,000, 4,000 and 5,000 Kelvin light color temperature
- 3 housing sizes available

ODEN LED Specifications



Project Name:

Catalog Number:

Type:

With six interchangeable caps and spun shade styles, the Oden - LED offers architects, designers and engineers endless possibilities for a custom fixture to fit their unique application.

The Oden - LED Arrays high-quality, durable construction makes it an ideal fixture for any application.

Ordering Information

MODEL	OPTICS	LEDs	CURRENT	KELVIN	VOLTAGE	MOUNTING	FINISH	CAP/SHADE	OPTIONS
ODN-1-L	T1	16LC	3	3K	UNV <small>*120-277V</small>	YM Yoke Mount *Slips over 3"ØD tenon x 4" tall with special threaded mounting plate.	BZ Bronze	C1	PC-120 Button Type Photocell
	T2	32LC	350mA	4K					8 347V
	T3	48LC	5	4000K	5 480V	AM Arm Mount Size 1 AML Arm Mount Large Size 2 & 3 See decorative arm section for arm & wall mount options. Decorative arm required for AM & AML	BK Black SBK Smooth Black	C3 C4 C5 C6	PC-240 Button Type Photocell
	T4		7	5K					WSC-8 Motion Sensor 8' Mounting Height
	T5		700mA	5000K					WSC-20 Motion Sensor 9-20' Mounting Height
ODN-2-L		48LC						H1 H2 H3 H4 H5 H6	WSC-40 Motion Sensor 21-40' Mounting Height This option will require (1) FSIR 100 remote for programming
		64LC				WH White			DIM 0-10v Dimming Driver
		80LC				SWH Smooth White			VWC Visionaire Wireless Controls *Consult Factory
		96LC				GP Graphite			IR-R Illuminated Rings Red
ODN-3-L		96LC				GY Grey		IR-B Illuminated Rings Blue	
		128LC				SL Silver Metallic		IR-G Illuminated Rings Green	
						FG Forest Green		CLS Cutoff Louver Shield	
						VD Verdigris			
						CC Custom Color			

Housing

- High-quality, one-piece spun aluminum shade and durable cast aluminum top cap; available in three housing sizes.
- All external hardware is stainless steel.
- One-piece spun aluminum removable door assembly..

Thermal Management

- The Oden - LED provides excellent overall thermal management by maximizing the efficiency of the heat sink in the fixture. This enables the Oden - LED to withstand higher ambient temperatures and higher drive currents without degrading LED life.

Optical System

- The highest lumen output LEDs are utilized. Estimated life of the LEDs is 100,000+ hours. Available with 6 IES distribution patterns. Available with up to 96 LED. The optical system qualifies as IES full cutoff to restrict light trespass, glare and light pollution for neighborhood-friendly lighting.
- CRI values are 70

Quali-Guard® Finish

- Fixture components are chemically pretreated through a multiple-stage washer and finished with an electrostatically-applied, thermoset polyester powder coat textured paint with a 3 to 5 mils thickness. Finish is oven-baked at 400 °F for maximum adherence and finish hardness.
- Available in standard and custom colors.

Mounting

- The Oden - LED mounts to a wide selection of decorative and custom Visionaire mounting arms. Visionaire decorative mounting arm required. See Visionaire Mounting Arms section of catalog.

Electrical Assembly

- The Oden - LED is supplied with a high-performance LED driver, located in its cap, that accepts 120 V thru 277 V, and 480 V, 50 Hz to 60 Hz input. Power factor is 90%.
- Rated for -40 of operation.
- 10 kV surge protector supplied as standard.

Warranty

- Five (5) year Limited Warranty on entire system, including finish. For full warranty information, please visit www.visionairelighting.com.

Options

- Button type photocell
- Watt Stopper FSP-211
- 0-10 V dimming driver
- Wireless Controls
- Illuminated Rings
- Cutoff louver system

Listings

- Oden is cUL listed, suitable for wet locations.
- IP65 Rated
- DLC Listed
- IDA Certification
- LM79
- LM80
- Powder Coated Tough™



DesignLights Consortium (DLC) qualified Product. Some configurations of this product family may not be DesignLights Consortium (DLC) listed, please refer to the DLC qualified products list to confirm listed configurations. <http://www.designlights.org/>
3000K must be selected for IDA certification.

ODEN LED Specifications

Photometric Optical Summary

Not all optics are available on all fixtures. Check ordering chart for availability

Type I
(T1)



Type II
(T2)



Type III
(T3)



Type IV
(T4)



Type V
(T5)



Type VW
(T5W)



EPA Data

Fixture	Fixture Only	Fixture with VA110-S1	2 Fixtures with VA110-D2	Fixture with VA107-S1	2 Fixtures with VA107-D2
ODN-1	1.2	2.2	4.1	3.5	5.6
ODN-2	2.6	3.6	6.6	4.9	8.3
ODN-3	3.5	4.5	8.6	5.8	9.8

Dimensions

Size 1

Width: ODN-1 20"

Height: ODN-1 19.5"

Weight: 40 LBS

Size 2

Width: ODN-2 25"

Height: ODN-2 22.5"


Weight: 53 LBS

Size 3


Width: ODN-3 30"

Height: ODN-3 24"


Weight: 74 LBS




CAP 1 (C1)




CAP 2 (C2)




CAP 3 (C3)




HOUSING 1 (H1)




HOUSING 2 (H2)




HOUSING 3 (H3)




CAP 4 (C4)




CAP 5 (C5)




CAP 6 (C6)




HOUSING 4 (H4)



HOUSING 5 (H5)



HOUSING 6 (H6)



4K Lumen Data <small>Lumen Chart Updated 11.20.17</small>																																	
	# LEDs	mA	Type 1	B	U	G	LPW	Type 2	B	U	G	LPW	Type 3	B	U	G	LPW	Type 4	B	U	G	LPW	Type 5	B	U	G	LPW	Type 5W	B	U	G	LPW	Watts
ODN-1	16	350	2561	1	0	1	142	2399	1	0	1	133	2443	1	0	1	136	2288	1	0	1	127	2568	1	0	1	143	2486	2	0	1	138	18
		530	3665	2	0	2	134	3433	1	0	1	126	3496	1	0	1	128	3275	1	0	1	120	3675	2	0	1	134	3558	2	0	1	130	27
		700	4572	2	0	2	124	4283	1	0	2	116	4361	1	0	1	118	4085	1	0	1	110	4585	2	0	1	124	4438	2	0	1	120	37
	32	350	4875	2	0	2	135	4566	1	0	2	127	4649	1	0	1	129	4355	1	0	1	121	4888	2	0	1	136	4732	3	0	1	131	36
		530	7225	3	0	3	132	6767	2	0	2	124	6891	1	0	1	126	6455	1	0	2	118	7245	3	0	1	133	7013	3	0	1	128	55
		700	9013	3	0	3	129	8442	2	0	2	121	8596	1	0	2	123	8053	2	0	2	115	9037	3	0	1	129	8748	3	0	2	125	70
	48	350	7701	3	0	3	144	7213	2	0	2	135	7345	1	0	1	137	6880	1	0	2	129	7722	3	0	1	144	7474	3	0	1	140	54
		530	11414	3	0	3	139	10690	2	0	3	130	10886	2	0	2	133	10198	2	0	2	124	11445	3	0	1	140	11078	3	0	2	135	82
		700	14237	3	0	3	133	13335	3	0	3	125	13580	2	0	2	127	12721	2	0	2	119	14276	3	0	2	133	13819	4	0	2	129	107
ODN-2	48	350	7701	3	0	3	144	7213	2	0	2	135	7345	1	0	1	137	6880	1	0	2	129	7722	3	0	1	144	7474	3	0	1	140	54
		530	11414	3	0	3	139	10690	2	0	3	130	10886	2	0	2	133	10198	2	0	2	124	11445	3	0	1	140	11078	3	0	2	135	82
		700	14237	3	0	3	133	13335	3	0	3	125	13580	2	0	2	127	12721	2	0	2	119	14276	3	0	2	133	13819	4	0	2	129	107
	64	350	10058	3	0	3	140	9421	2	0	3	131	9593	2	0	2	133	8986	2	0	2	125	10085	3	0	1	140	9763	3	0	2	136	72
		530	14224	3	0	3	135	13323	3	0	3	127	13567	2	0	2	129	12709	2	0	2	121	14263	3	0	2	136	13807	4	0	2	131	105
		700	17919	4	0	4	128	16784	3	0	3	120	17091	2	0	2	122	16011	3	0	3	114	17969	4	0	2	128	17393	4	0	2	124	140
	80	350	12294	3	0	3	138	11515	3	0	3	129	11726	2	0	2	132	10984	2	0	2	123	12328	3	0	2	139	11933	4	0	2	134	89
		530	17187	3	0	3	132	16098	3	0	3	124	16393	2	0	2	126	15356	3	0	3	118	17234	4	0	2	133	16683	4	0	2	128	130
		700	21635	4	0	4	122	20265	3	0	4	114	20636	3	0	3	117	19331	3	0	3	109	21695	4	0	2	123	21000	4	0	2	119	177
	96	350	14832	3	0	3	136	13892	3	0	3	127	14146	2	0	2	130	13252	2	0	2	122	14872	3	0	2	136	14396	4	0	2	132	109
		530	21334	4	0	4	133	19982	3	0	3	125	20348	3	0	3	127	19061	3	0	3	119	21392	4	0	2	134	20707	4	0	2	129	160
		700	26644	4	0	4	127	24956	3	0	4	119	25412	3	0	3	121	23805	3	0	3	113	26717	4	0	2	127	25861	5	0	3	123	210
ODN-3	96	350	14832	3	0	3	136	13892	3	0	3	127	14146	2	0	2	130	13252	2	0	2	122	14872	3	0	2	136	14396	4	0	2	132	109
		530	21334	4	0	4	133	19982	3	0	3	125	20348	3	0	3	127	19061	3	0	3	119	21392	4	0	2	134	20707	4	0	2	129	160
		700	26644	4	0	4	127	24956	3	0	4	119	25412	3	0	3	121	23805	3	0	3	113	26717	4	0	2	127	25861	5	0	3	123	210
	128	350	18258	4	0	4	127	17101	3	0	3	119	17415	2	0	2	121	16313	3	0	3	113	18308	4	0	2	127	17722	4	0	2	123	144
		530	25821	4	0	4	123	24186	3	0	4	115	24628	3	0	3	117	23071	3	0	3	110	25892	4	0	2	123	25063	5	0	3	119	210
		700	32530	5	0	4	119	30469	4	0	5	111	31026	3	0	4	113	29064	3	0	4	106	32619	5	0	3	119	31574	5	0	3	115	274

Visit www.VisionaireLighting.com for up-to-the-minute chart information, including types not listed here. *Multiply 4K values by 0.96 5K/0.95 3K



 **VISIONAIRE**
L I G H T I N G

19645 Rancho Way . Rancho Dominguez, CA 90220
310.512.6480
www.visionairelighting.com