



**The Lusso Collection** powered by ARRAY from Visionaire Lighting can elegantly compliment the daytime architecture of your space, while providing nighttime illumination that is up to task and equally as elegant. The collection consists of a wall sconce, bollard, single or twin arm post top and a beautiful pole mount. Available in two housings sizes and lumen packages up to 55,000 lumens thanks to our performance ARRAY LED platform. Scale and design creativity has no limits for any application.

## Lusso Medium Post Top



### Key Features

- Cast aluminum housing
- IP65 Housing and LED optical assembly
- 400 W Replacement
- 10 Specification Grade low glare optics
- 5,000 – 27,000 lumen packages
- 52 – 200 wattage range
- 120-277 universal Drivers, 347 & 480 voltage drivers
- 10KV Surge Protector
- 90% Power Factor
- 10 Year Electrical Warranty
- PangeaLink compatible
- Cantilever and Yoke Mount Design
- Mounts over 3" OD tenon
- 3, 5 and 7 Photocell receptacles
- 0-10V Dimming driver
- Title 24 Compliant Motion Sensor



# LUSSO ARRAY M-PT LED Specifications



Project Name: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Type: \_\_\_\_\_

Contemporary design meets the new generation of LED green technology in this stunning luminaire, the **Lusso Array**. The Lusso Array series provides over fifty percent energy savings over traditional HID light sources; and offers excellent beam control and LED life beyond 100,000 hours for 1400 milliamp systems. The Lusso Array is offered in ten optical distributions.

The Lusso Array's fully-sealed housing features an exceptionally well-designed thermal management system that provides superior heat dissipation.

The Lusso Array fixture is built with cast aluminum.

The **Lusso Array** is the perfect compliment to any university campus, business park, or walkway project where contemporary, architectural design is desired.

## Ordering Information

MODEL	OPTICS	LUMENS	KELVIN	VOLTAGE	MOUNTING	FINISH	OPTIONS	OPTIONS	
LSO-M	<b>T1</b> Type 1	<b>5L</b>	<b>3K</b> 3000K	<b>UNV</b> 120-277V	<b>PTS</b> Post Top Single Arm	<b>BK</b> Black	<b>PCR-120</b> Photocell & Receptacle	<b>VWC</b> Visionaire Wireless Controls Consult Factory	
	<b>T2</b> Type 2	<b>10L</b>	<b>4K</b> 4000K	<b>8</b> 347V		<b>SBK</b> Smooth Black	<b>PCR-208</b> Photocell & Receptacle		<b>ROT-R</b> Rotated Optics Right Side
	<b>T3</b> Type 3	<b>15L</b>	<b>5K</b> 5000K	<b>5</b> 480V	<b>PTD</b> Post Top Double Arm	<b>BZ</b> Bronze	<b>PCR-240</b> Photocell & Receptacle	<b>ROT-L</b> Rotated Optics Left Side	
	<b>T3L</b> Type 3 Long	<b>20L</b>				<b>GP</b> Graphite	<b>PCR-277</b> Photocell & Receptacle		
	<b>T4</b> Type 4	<b>25L</b>			The Lusso Medium Post Top will slip over a 3" O.D. X 4" Tall tenon	<b>GY</b> Grey	<b>PCR-480</b> Photocell & Receptacle		
	<b>T4A</b> Type 4 Automotive					<b>SL</b> Silver Metallic	<b>PER</b> 3 Pin Photo Receptacle w/shorting cap	<b>5PINPER</b> 5 Pin Photo Receptacle w/shorting cap Requires Dimming Driver	
	<b>T4L</b> Type 4 Long					<b>WH</b> White	<b>7PINPER</b> 7 Pin Photo Receptacle w/shorting cap Requires Dimming Driver	<b>DIM</b> 0-10v Dimming Driver	
	<b>T5LR</b> Type 5 Long Round					<b>SWH</b> Smooth White	<b>FG</b> Forest Green	<b>WSC-8</b> Motion Sensor 8' Mounting Height	
	<b>T5LS</b> Type 5 Long Square					<b>VD</b> Verdigris Green	<b>WSC-20</b> Motion Sensor 9-20' Mounting Height		
	<b>T5SR</b> Type 5 Short Round					<b>CC</b> Custom Color	<b>WSC-40</b> Motion Sensor 21-40' Mounting Height		

The WSC option will require  
(1) FSIR 100  
remote for programming