



The Lusso Collection powered by ARRAY from Visionaire Lighting can elegantly compliment the daytime architecture of your space, while providing nighttime illumination that is up to task and equally as elegant. The collection consists of a wall sconce, bollard, single or twin arm post top and a beautiful pole mount. Available in two housings sizes and lumen packages up to 55,000 lumens thanks to our performance ARRAY LED platform. Scale and design creativity has no limits for any application.

Lusso Sconce



Key Features

- Cast aluminum housing
- IP65 Housing and LED optical assembly
- 6 Specification Grade low glare optics
- Serenity High and Low Diffused lens
- 1,000 – 5,000 lumen packages
- 13 – 45 wattage range
- 120-277 universal Drivers
- 10KV Surge Protector
- 90% Power Factor
- Cantilever and Yoke Mount Design
- 5 Year Electrical Warranty
- Button Style Photocell
- 0-10V Dimming driver
- PangeaLink compatible

LUSSO Sconce LED Specifications



Project Name:

Catalog Number:

Type:

The **Lusso Sconce LED** Series continues the unique contemporary design inspired by the sleek styling of the Lusso family. Separating the Driver(s) from the individual die-cast aluminum LED engines: optimize the life of the LEDs and the Driver(s); and maximizes the lumen output of the fixture.

Four optical distribution patterns are available. Choose between 3K, 4K or 5K Kelvin temperature of the LED's.

A durable polyester powdercoat finish is guaranteed for five years; and is available in standard or custom colors.

The **Lusso Sconce LED** Series is an exceptional choice for low level lighting applications.

Ordering Information

MODEL	OPTICS	SOURCE	CURRENT	KELVIN	VOLTAGE	MOUNTING	FINISH	OPTIONS
LSO-S	T1 Type 1	20LC	1 175mA	3K 3000K	UNV 120-277V	WM-PTD Wall Mount Post Top Double Arm	BK Black	PC-120 Button Type Photocell
	T2 Type 2		3 350mA	4K 4000K			SBK Smooth Black	PC-208 Button Type Photocell
	T3 Type 3		5 530mA	5K 5000K			BZ Bronze	PC-240 Button Type Photocell
	T4 Type 4		7 700mA				GP Graphite	PC-277 Button Type Photocell
							GY Grey	DIM 0-10v Dimming Driver
							SL Silver Metallic	LDL Lightly Diffused Lens
							WH White	HDL High Diffused Lens
			SWH Smooth White	VD Verdigris Green				
			FG Forest Green	CC Custom Color				