

DCB-3

Project Name:

Catalog Number:

Type



Model	Shaft Diameter	Finish
DCB-3	4" O.D. Smooth (4RS)	Bronze (BZ)
	5" O.D. Smooth (5RS)	Black (BK)
	6" O.D. Smooth (6RS)	White (WH)
		Forest Green (FG)
		Grey (GY)
		Silver Metallic (SL)
		Custom Color (CC)


Fluted aluminum, smooth aluminum or smooth steel poles only. See pole specification sheet for details.

Base

- Two piece decorative fluted cast aluminum pole base.

Finish

• All bases are shot-blasted and cleaned to a near-white finish prior to painting. A Quali-Guard® textured thermoset polyester powder coat is then applied to a minimum of 3 millimeters and then oven-baked at a temperature of 400 °F to promote exceptional adherence and finish hardness. Base finish is warranted for a full two (2) years. An optional five (5) year extended warranty is also available.



DCB-4




Model	Shaft Diameter	Finish
DCB-4	4" O.D. Smooth (4RS)	Bronze (BZ)
	5" O.D. Smooth (5RF)	Black (BK)
		White (WH)
		Forest Green (FG)
		Grey (GY)
		Silver Metallic (SL)
		Custom Color (CC)

Base

- Two piece decorative fluted cast aluminum pole base.

Finish

• All bases and poles are shot-blasted and cleaned to a near-white finish prior to painting. A Quali-Guard® textured thermoset polyester powder coat is then applied to a minimum of 3 millimeters and then oven-baked at a temperature of 400 °F to promote exceptional adherence and finish hardness. Pole finish is warranted for a full two (2) years. An optional five (5) year extended warranty is also available.



For more detailed information on mounting, wiring or installation instructions, please consult factory. If poles are not ordered with fixtures, please specify mounting requirements. This document contains proprietary information of Visionaire Lighting, LLC. Any use of this information requires the written approval of Visionaire Lighting, LLC. In keeping with our TQM policy of continuous improvement, Visionaire reserves the right to change any specifications contained herein without prior notice.