



The **V Collection** powered by ARRAY from Visionaire Lighting can elegantly compliment the daytime architecture of your space while providing nighttime illumination that is up to the task and equally as elegant. The collection consists 4 sizes of site lighting fixture, 2 wall mounts and a bollard. Available with our ARRAY LED platform. Scale and design creativity has no limits for any application.

VSX-II Array



Key Features

- Die Cast aluminum housing
- IP65 Housing and LED optical assembly
- 400 W Replacement
- Six New Versatile Mounts (UAM, SAM, AM, KM, MAF, AWM)
- Seven Comprehensive Shields (CLS, R-CLS, L-CLS, ADJLS, EGLS, HS, BD)
- Two Levels of Visual Comfort (LDL - Low Diffused and HDL - High Diffused)
- 10 Specification Grade low glare optics
- 5,000 – 25,000 lumen packages
- 34 - 167wattage range
- 120-277 universal Drivers, 347 & 480 voltage drivers
- 10KV Surge Protector
- 90% Power Factor
- 10 Year Electrical Warranty
- PangeaLink compatible
- Quick Mount Cleat
- Mounts to round or square pole
- 3, 5 and 7 Photocell receptacles
- 0-10V Dimming driver
- Title 24 Compliant Motion Sensor

VSX-II Mounting Options



VSX-II Array LED Specifications



*Universal Arm Mount (UAM) Version Shown.

Project Name:

Catalog Number:

Type:

The new **VSX-II Array LED** Series offers clean, functional styling that is defined by its sleek low profile design and rugged construction. It combines the latest LED Array technology, advanced LED thermal management and provides outdoor lighting that is both energy efficient and aesthetically pleasing.

The LED's performance and the driver's life are maximized by enclosing them in two separate die cast aluminum housings.

The VSX-II Array LED fixture is offered with lumen packages ranging from 5,000 - 25,000. Ten optical distribution patterns are available. Choose between 3000, 4000 or 5000 Kelvin temperature of the LEDs.

A durable polyester powder coat finish is guaranteed for five years; and is available in standard or custom colors.

The **VSX-II Array LED** series is an exceptional choice for commercial parking lots, office complexes, architectural projects, and other general lighting projects.

Ordering Information

MODEL	OPTICS	LUMENS	KELVIN	VOLTAGE	MOUNTING	FINISH	OPTIONS	OPTIONS	OPTIONS
VSX-II	T1 Type 1	5L	3K 3000K	UNV 120-277V	AM Arm Mount	BZ Bronze	PCR-120	WSC-8 Motion Sensor 8' Mounting Height	UPMA-S Universal Square Pole Mount Adaptor
	T2 Type 2	10L	4K 4000K	8 347V	SAM Straight Arm Mount W/ Terminal Block (New Construction)	BK Black	PCR-208		
	T3 Type 3	15L	5K 5000K	5 480V		SBK Smooth Black	PCR-240	WSC-20 Motion Sensor 9-20' Mounting Height	UPMA-R Universal Round Pole Mount Adaptor
	T3L Type 3 Long	20L			UAM Universal ArmW/ Terminal Block Mount (Retrofit)	WH White	PCR-277		
	T4 Type 4	25L			MAF Mast Arm Fitter	SWH Smooth White	PCR-347	WSC-40 Motion Sensor 21-40' Mounting Height *The WSC option will require (1) FSIR 100 remote for programing	BAWP Cast Wall Plate
	T4L Type 4 Long				KM Knuckle Mount	GP Graphite	PCR-480 Photocell & Receptacle		ROT-R Rotated Optics Right Side
	T4A Type 4 Automotive				WM Wall Mount *Requires BAWP	GY Grey	PER	UMAP Universal Mast arm fitter	ROT-L Rotated Optics Left Side
	T5SR Type 5 Short Round				AWM Adjustable Wall Mount	SL Silver Metallic	5PINPER 3, 5, or 7 Pin Photo Receptacle w/shorting cap Requires Dimming Driver	ECLS Egg Crate Louver Shield	CLS Backside cutoff shield
	T5LR Type 5 Long Round				*Round Pole Plate Adaptors (RPP) are to be ordered separately.	CC Custom Color	7PINPER 3, 5, or 7 Pin Photo Receptacle w/shorting cap Requires Dimming Driver	RPP Round Pole Plate Adaptor	RCLS Rightside cutoff shield
	T5LS Type Long Square				*BAWP to be ordered separately		DIM 0-10v Dimming Driver	VWC Visionaire Wireless Controls *Consult Factory	LCLS Leftside cutoff shield
								ADJLS Adjustable Louver Light Shield	HS House shield
								BD Barn Door Shield	