



The Lusso Collection powered by ARRAY from Visionaire Lighting can elegantly compliment the daytime architecture of your space, while providing nighttime illumination that is up to task and equally as elegant. The collection consists of a wall sconce, bollard, single or twin arm post top and a beautiful pole mount. Available in two housings sizes and lumen packages up to 55,000 lumens thanks to our performance ARRAY LED platform. Scale and design creativity has no limits for any application.

Lusso Large Post Top



Key Features

- Cast aluminum housing
- IP65 Housing and LED optical assembly
- 1000 W Replacement
- 10 Specification Grade low glare optics
- 25,000 – 55,000 lumen packages
- 202 - 408 wattage range
- 120-277 universal Drivers, 347 & 480 voltage drivers
- 10KV Surge Protector
- 90% Power Factor
- 10 Year Electrical Warranty
- PangeaLink compatible
- Cantilever and Yoke Mount Design
- Mounts over 4"OD pole
- 3, 5 and 7 Photocell receptacles
- 0-10V Dimming driver
- Title 24 Compliant Motion Sensor

LUSSO ARRAY L-PT LED Specifications



Project Name:

Catalog Number:

Type:

Contemporary design meets the new generation of LED Array green technology in this stunning luminaire, the **Lusso Array**. The Lusso Array is offered in ten optical distributions.

The Lusso Array's fully-sealed housing features an exceptionally well-designed thermal management system that provides superior heat dissipation.

The Lusso Array fixture is built with cast aluminum.

The new **Lusso Array** is the perfect compliment to any university campus, business park, or walkway project where contemporary, architectural design is desired.

Ordering Information

MODEL	OPTICS	LUMENS	KELVIN	VOLTAGE	MOUNTING	FINISH	OPTIONS	OPTIONS	
LSO-L	T1 Type 1	25L	3K 3000K	UNV 120-277V	PTS Post Top Single Arm	BK Black	PCR-120 Photocell & Receptacle	VWC Visionaire Wireless Controls Consult Factory	
	T2 Type 2	30L	4K 4000K	8 347V			SBK Smooth Black		PCR-208 Photocell & Receptacle
	T3 Type 3	35L	40L 5000K	5 480V	PTD Post Top Double Arm The Lusso Post Top will slip over a 4" O.D. X 4" Tall tenon	BZ Bronze	PCR-240 Photocell & Receptacle	ROT-L Rotated Optics Left Side	
	T3L Type 3 Long	45L	5K				GP Graphite		PCR-277 Photocell & Receptacle
	T4 Type 4	50L					GY Grey		PCR-480 Photocell & Receptacle
	T4A Type 4 Automotive	55L					SL Silver Metallic		PER 3 Pin Photo Receptacle w/shorting cap
	T4L Type 4 Long						WH White		5PINPER 5 Pin Photo Receptacle w/shorting cap Requires Dimming Driver
	T5LR Type 5 Long Round						SWH Smooth White		7PINPER 7 Pin Photo Receptacle w/shorting cap Requires Dimming Driver
	T5LS Type 5 Long Square						FG Forest Green		DIM 0-10v Dimming Driver
	T5SR Type 5 Short Round						VD Verdigris Green		WSC-8 Motion Sensor 8' Mounting Height
							CC Custom Color		WSC-20 Motion Sensor 9-20' Mounting Height
									WSC-40 Motion Sensor 21-40' Mounting Height

The WSC option will require
(1) FSIR 100
remote for programming